

## Wireless Network Connector adds Schneider and RLE device support







No more "stranded" metered devices! Packet Power's Wireless Network Connector (WNC) is an easy way to make select metered devices work over Packet Power's wireless network. Plug the WNC into the Ethernet or serial port of a supported device and data will automatically flow across the wireless network.

## **Features**

- Detects certain metered devices from APC, Geist, RLE, Schneider and Servertech (recently added devices noted in blue below)
- Instantly connects to Packet Power's self-configuring, self-optimizing wireless mesh network
- Use the local LCD display to immediately verify correct operation
- Supports up to 2 optional temperature probes
- Can be mounted with a low profile bracket, via a DIN rail clip, or by optional magnet
- Powered by external 100-240V power supply (works with most plug types including C13); some power strips can power the WNC directly from USB or other ports
- Support for other brands of power strips as well as standalone meters, UPSs, RPPs/PDUs, ATSs, Gensets and others will be added over time; contact Packet Power to discuss

Pricing varies by end device type supported. Contact Packet Power for details.

Brand	Models*	
APC	Supported AP77XX, 78XX, 79XX and 88XX models	
Geist	Power strips using IMD-02 and IMD-03 meter platforms	
RLE	LDRA6 multi-zone leak detection controllers	
Schneider	PM5XXX power meters	
Servertech	Supported PRO2 CDUs	

<sup>\*</sup> May not be compatible with all firmware release levels and configuration settings

## Easy access to data

Customers with existing monitoring applications can access data sent by the WNC via a Packet Power Ethernet Gateway using standard protocols such as SNMP, Modbus and Ethernet/IP. Packet Power's EMX Energy Portal provides an easy to use option for customers that have yet to deploy a monitoring application.

For more information go to: www.packetpower.com/network-integration